

## Test Certificate 137560 - 1

### Report Details

<b>Report Number</b>	137560 - 1	<b>Date Tested</b>	02-Jun-26	<b>Date Issued</b>	09-Jun-26
<b>Service Requested</b>	BS 5852 Part 2: 1982 - Schedule 1 Part 3				

### Customer Details

<b>Company Name</b>	FIBRELINE LTD		
<b>Customer Contact</b>	MARC RADCLIFFE	<b>Company Address</b>	VICTORIA PARK MILLS
<b>Customer Ref/PO</b>	FL050526		HARD INGS ROAD
			KEIGHLEY
			BD21 3ND

### Sample Details - As Supplied by the Customer

**Sample Description** LATEX FOAM

**Fibre Composition**

**Quality/Batch Ref** FL081225

**Colour**

**Sample End Use**

**Model Ref**

**Manufacturer**

**Density / Layers**

/

**Supplier / Buyer**

### Specification:

Schedule 1 Part 3 (Ignitibility test for Latex Rubber) of The Furniture Furnishings (Fire) (Safety) Regulations 1988 (as amended). S.I. 1324

### Test Methods:

BS 5852 Part 2: 1982 Source 2 - Methods of test for the ignitibility of upholstered composites for seating by flaming sources.

### Conditioning:

The sample was conditioned for 72 hrs in ambient conditions then for at least 24 hrs in a specified atmosphere at  $20 \pm 5^{\circ}\text{C}$  and  $50 \pm 20\%$  relative humidity.

### Test Results

The Following test results relate only to the ignitibility of the combination of the materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.

Test Criteria	Initial Test		Repeat Test	
*Flaming / Glowing / Smoke Ceased:	0.52	0.00	0.19	0.00
<b>Progressive Smouldering Criteria</b>				
*Detectable amounts of smoke, heat or glowing 60 minutes after ignition?	<input type="checkbox"/>		<input type="checkbox"/>	
Displays unsafe escalating combustion and requires forcibly extinguishing?	<input type="checkbox"/>		<input type="checkbox"/>	
Smouldering consumed the test specimen within the duration of the test?	<input type="checkbox"/>		<input type="checkbox"/>	
Smoulder to the Extremities? I.E Upper or Lower margins, either side or to its full thickness	<input type="checkbox"/>		<input type="checkbox"/>	
*On final inspection, any evidence of charring more then 100mm in any direction (apart from upwards) from the original nearest position?	<input type="checkbox"/>		<input type="checkbox"/>	
<b>Flaming Criteria</b>				
*Flaming for more then 120 Seconds:	<input type="checkbox"/>		<input type="checkbox"/>	
Displays unsafe escalating combustion?	<input type="checkbox"/>		<input type="checkbox"/>	
Flaming and/or smouldering consumed the test specimen within the duration of the test?	<input type="checkbox"/>		<input type="checkbox"/>	
Flame front reaches the upper or lower margin, either side or passes through the full thickness?	<input type="checkbox"/>		<input type="checkbox"/>	
<b>Test Result</b>	<b>PASS</b>		<b>PASS</b>	

**Overall Result: PASS**

The sample supplied meets the requirements of Schedule 1 Part 3 (Ignitibility test for Latex Rubber) of The Furniture & Furnishings (Fire) (Safety) Regulations 1988 (as amended). S.I. 1324

Authorised Signature:



**John Furnival**

Processing Manager

Please note: The uncertainty of measurement is taken into account when stating conformance to the specification. The measured value(s) marked\* are compared with the 'acceptance interval' which is determined by reducing the specification limits by the expanded test uncertainty  $U_{k=2}$  (approximately 95% confidence interval). And providing all measured values are within the tolerance limits then such results are declared as "Pass". The Uncertainty budgets are stated for each test method and should be considered when results are on or close to the acceptance limits, and in such cases it should be noted that the risk of false acceptance or false rejection is  $\leq 2.5\%$ . Results outside these limits are declared as 'fail'. All test results issued on this report refer only to the item under test as supplied by the customer. This certificate shall not be reproduced, unless in its entirety, without written approval from IFS Laboratories Ltd

**END OF REPORT**